



LASTRA PVC FLESSIBILE KRISTALL

PVC STRIP TECHNICAL MATERIAL DATA

Properties	Standard	PVC Strip Grade (Normal Tempt Grade)	PVC Strip Grade (Low Tempt Grade)	Unit
Density	DIN 53 479	1.22	1.19	g/cm3
Shore A Hardness	DIN 53 505	77	63	A
Brittle Point	DIN 53 372	Approx -35	Approx -45	Degrees °C
Falling Ball Test	Internal Test	"-35 No Break	"-45 No Break	Degrees °C
Flexibility	DIN 51 949	"-35 No Break	"-45 No Break	Degrees °C
Water Absorption	DIN 53 472	17	21	Mg
Tensile Strength	DIN 53 455	17	13	Mpa
Tensile Stress	DIN 53 455	300	420	%
Rupture Resistance	DIN 53 515	>5	>2	N/mm
Reaction to Fire	DIN 53 382	Self-distinguishing	Self-distinguishing	0
Flammability	Based on US MV SS302	Inflammable	Inflammable	0
Light Transmission		>80	>80	%

Fratelli Ceni spa
 Via Galileo Galilei, 551, 37040, Zimella
 Tel +39 0442 489611 Fax +39 0442 489641
 P.iva 02054430232